

PRODUCT DESCRIPTION



1. High-pressure atomizing nozzle

American brand original nozzle, removable for cleaning


4. Pretreatment liquid color switching valve

Simple control and clear goals



2. display screen

- ① Support display content Chinese/English switching
- ② set sprays volume The spraying ink volume is adjustable from 10ml-100ml, and the spraying volume can be flexibly set according to the characteristics of different fabrics. The light-colored T-shirt is set to 40ml, and the dark-colored T-shirt is set to 45ml, which is the best solution (factory setting solution)
- ③ The nozzle cleaning function effectively avoids the nozzle clogging after the work is over, and the color mixing caused by the residual pretreatment liquid of different colors
- ④ Record the spraying time of each T-shirt and the number of sprayed T-shirts, so that you can clearly manage your work efficiency (click to clear)
- ⑤ Dark and light pretreatment liquid can be switched at will, and the color of the treatment liquid currently set to be sprayed will be displayed to let you know your choice



5. Spray area regulating valve

Save liquid, the maximum spraying range 50cm adjustable



6. Waste discharge pipe

Release waste liquid to avoid corrosion



3. Built-in liquid bottle

Pretreatment liquid bottle: 2*5000ml
cleaning liquid bottle: 1*1000ml



7. Extension catheter

Save the time of transferring liquid to the built-in bottle



DTG pretreatment machine

| | |
|----------------------------------|--|
| DIRECT-TO-TEXTILE | yes |
| NUMBER OF SPRAY NOZZLE | 1pcs |
| NOZZLE TECHNOLOGY | High pressure atomization spray technology |
| NOZZLE BRAND | The United States imported nozzle |
| NOZZLE CONTROL TECHNOLOGY | Automatic flow drop control |
| CONTROL FIRMWARE SYSTEM | PLC programming system |
| SPRAY SPEED | Light color :5 seconds/1 T-shirt, 40ml; Dark 6 seconds/1 T-shirt 45ml (520mm x 420mm size) |
| SPRAY PATH WIDTH | 40cm |
| SPRAY PATH LENGTH | Adjustable up to 50mm |
| STANDARD PLATEN SIZE | 520mm x 420mm |
| SPRAY PATH MOTION | Bi-Direction |
| SPRAY FLOW | 10ml~ 100ml Adjustable |
| LIQUID CHANNEL | 3 Types (dark T-shirt pretreatment, light T-shirt pretreatment, cleaning fluid) |
| LIQUID CONVERT | Automatic electromagnetic valve control |
| LIQUID TANK CAPACITY | Pretreatment Liquid Tank:2000ml*2pcs Cleaning liquid tank:1000ml*1pcs |
| ELECTRICAL REQUIREMENTS | 220V/110V (50HZ/60HZ) 150W |
| TRANSMISSION TYPE | Linear rail |
| NET WEIGHT | 59Kg |
| PACKING WEIGHT | 90Kg |
| MACHINE SIZE | 905*580*750mm |
| PACKING SIZE | 955*625*880mm |

Why choose DTG pretreatment machine

- The operation is simple, all on a smart screen, just like using a mobile phone, it is easy to use.
- The automatic pre-treatment machine from an expert DTG printer manufacturer for consistency in repeated jobs and improved washability, while saving on liquids.
- An easy-to-use, safe and efficient pretreatment machine that is the key to achieving top-quality printing results.
- The ideal automatic pre-treatment machine for any dtg printing businesses.